

PRODUCT INFORMATION

WELDABILITY FLOWMETRE

AU200
AU300

SUMMARY

Designed to be fitted to the outlet of an argon or CO2 regulator to provide greater control of the flow of your shielding gas through the gas line.

TARGET APPLICATIONS

Flowmeters are designed for use with shielding gases used in MIG welding applications. The accuracy of the gas flow control is greatly increased by use of a flowmeter fitted to the outlet of an argon-mix or CO2 regulator. It has the added benefit of giving a visual indication of when gas is actually flowing.



FURTHER INFORMATION

Ideal for use in MIG and TIG. 2 models are available, with either 0-15LPM or 0- 40LPM flow rate. Normal flow rate for MIG welding is 15-18 lpm.

ARTICLES & ACCESSORIES

Part Number	Product Description
AU200	Flowmeter 0-15lpm
AU300	Flowmeter 0-40lpm

TECHNICAL SPECIFICATION

AU200 Flow Rate	0-15 Litres Per Minute
AU300 Flow Rate	0-40 Litres Per Minute

For further information, contact Weldability | Sif technical support on **0870 330 7757** or email service@weldability-sif.com



Registered in England No. 1684362
Registered Office: as above

Doc Ref: WELDABILITY/PSI/AU200