



DISPOSABLE GAS CYLINDERS



PART NUMBERS	PRODUCT DESCRIPTIONS
TWN802038 TWN802038L	DIPSOSABLE CO ₂ CYLINDERS 390 GRAM 600 GRAM
TWN802048 TWN802048L	DIPSOSABLE ARGON/CO ₂ CYLINDERS 390 GRAM 600 GRAM
TWN802050 TWN802050L	DIPSOSABLE ARGON CYLINDERS 390 GRAM 600 GRAM

PICTURE FILE: TWN802038-50L

PRODUCT DESCRIPTION:

WWS disposable gas cylinders, intended for one use only, are manufactured to the highest quality by a hot-spinning process and are covered in an oven-curved epoxy coating to ensure reliability and safety beyond the criteria set out in BS 5188.

Incorporating a 1/8" BSP outlet fitting, these cylinders are compatible with most popular brands of portable MIG and TIG welding equipment and provide a handy, cost-effective alternative to stationary industrial sized gas cylinders.

Disposable cylinders containing CO₂, Argon/CO₂ mix and pure Argon are available from WWS. CO₂ and Argon/CO₂ are commonly used as shielding gases in MIG welding of mild steel and thin sheet metal. Pure Argon is popularly used as a shielding gas in general TIG welding and in MIG welding of non-ferrous metals.

WWS provide disposable cylinders in 390g and 600g sizes.

TECHNICAL SPECIFICATIONS:

	<u>CO₂</u>		<u>Argon/CO₂</u>		<u>Argon</u>	
	390g	600g	390g	600g	390g	600g
Outlet Fitting:	1/8" BSP		1/8" BSP		1/8" BSP	
Tare Weight:	1210g	1336g	1210g	1336g	1210g	1336g
Average Full Weight:	1600g	1936g	1302g	1460g	1304g	1414g
Volume:	700cc	835cc	700cc	835cc	700cc	835cc
Pressure:	60Bar	60Bar	60Bar	60Bar	60Bar	60Bar
Suitable Applications:	MIG welding mild steel and thin sheet metal		MIG welding mild steel and thin sheet metal		For general TIG and non-ferrous MIG welding	

NOTES:

All WWS disposable cylinders are manufactured to BS 5188 and have 1/8" BSP threaded outlet fittings.

ALTERNATIVES:

TEL: 01462 482200 FAX: 01462 482202 EMAIL: sales@wholeweld.co.uk
VISIT THE WHOLESALE WELDING SUPPLIES WEBSITE AT: <http://www.wholeweld.co.uk>