

# Extractability™

## PRODUCT INFORMATION

### ProtectoBench 1000/1500/2000/2500

#### SUMMARY

ProtectoBench 1000/1500/2000/2500 is a downdraught extraction bench with optional backdraught extraction. Protectobench is supplied to sit on the floor. The extraction bench removes hazardous smoke and dust at source.

Fumes & dust are extracted downwards and also to the back wall if this option is fitted. 90% of the extracted particles are pre-separated within the bottom section of the bench which can then be disposed by means of emptying the dust tray. ProtectoBench requires fan & filter system to be connected.

#### TARGET APPLICATIONS

Welding and grinding alloyed and unalloyed steels, precious metals, galvanised material.



#### FURTHER INFORMATION

Optional rear wall extraction, side panels, lamella curtain folding sides, wood supports.

#### ARTICLES & ACCESSORIES

Part Number	
PROTECTOBENCH1000	1m wide
PROTECTOBENCH1500	1.5m wide
PROTECTOBENCH2000	2m wide
PROTECTOBENCH2500	2.5m wide
EXT999200005	Lamella Sides

#### TECHNICAL SPECIFICATION

Extraction Capacity	Bench 1000 = 1500 m <sup>3</sup> /h Bench 1500 = 1800 m <sup>3</sup> /h Bench 2000 = 2300 m <sup>3</sup> /h Bench 2500 = 3000 m <sup>3</sup> /h
Rear Extraction	Bench 1000 = 150mm diameter Bench 1500 = 150mm diameter Bench 2000 = 2 x 150mm diameter Bench 2500 = 2 x 150mm diameter
Low Level Extraction	Bench 1000 = 180mm diameter Bench 1500 = 200mm diameter Bench 2000 = 224mm diameter Bench 2500 = 250mm diameter
Dimensions (LxWxH)	1000m x 1000mm x 850mm 1500m x 1000mm x 850mm 2000m x 1000mm x 850mm 2500m x 1000mm x 850mm  Back Wall & Sides 900mm (H ONLY)

For further information, contact Extractability technical support on **0845 862 2620** or email [service@extractability.eu](mailto:service@extractability.eu)