

## SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/6

### Sifalloy No 76

Revision 1

Revision date 2015-11-16

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Product name	Sifalloy No 76
Product code	RT76[12/16/24/32]25

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [SU15] Manufacture of fabricated metal products, except machinery and equipment; [PC38] Welding and soldering products (with flux coatings or flux cores.), flux products;
-------------	--

##### 1.3. Details of the supplier of the safety data sheet

Company	Weldability   Sif
Address	Peters House, The Orbital Centre, Icknield Way, Letchworth Garden City, Hertfordshire, SG6 1ET. UK.
Web	www.weldability-sif.com
Telephone	0870 330 7757
Fax	0800 970 7757
Email	service@weldability-sif.com
Email address of the competent person	msds@weldability-sif.com

##### 1.4. Emergency telephone number

Emergency telephone number	0870 330 7757
Company	Weldability Sif 8.30 - 5.30 Mon - Fri

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	T; R48/23 Xn; R40-42/43 R52/53 Symbols: T: Toxic.
Main hazards	Limited evidence of a carcinogenic effect. May cause sensitisation by inhalation and skin contact. Toxic: danger of serious damage to health by prolonged exposure through inhalation. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
2.1.2. Classification - EC 1272/2008	Skin Sens. 1: H317; Resp. Sens. 1: H334; Carc. 2: H351; STOT RE 1: H372; Aquatic Chronic 3: H412;

##### 2.2. Label elements

## Sifalloy No 76

Revision 1

Revision date 2015-11-16

## 2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Skin Sens. 1: H317 - May cause an allergic skin reaction. Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled. Carc. 2: H351 - Suspected of causing cancer . STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure . Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Precautionary Statement: Prevention	P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P270 - Do no eat, drink or smoke when using this product. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P284 - [In case of inadequate ventilation] wear respiratory protection.
Precautionary Statement: Response	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308+P313 - IF exposed or concerned: Get medical advice/attention. P314 - Get medical advice/attention if you feel unwell. P321 - Specific treatment (see on this label). P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER/doctor/ .
Precautionary Statement: Storage	P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to

## SECTION 3: Composition/information on ingredients

## 3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
nickel powder. .	028-002-01-4	7440-02-0	231-111-4			Carc. Cat. 3; R40 T; R48/23 R43 R52/53	
Chromium		7440-47-3	231-157-5				
Cobalt	027-001-00-9	7440-48-4	231-158-0			R42/43 R53	
Silicon		7440-21-3	231-130-8				
Copper (Copper fume)		7440-50-8	231-159-6				
aluminium powder (stabilised). . (Aluminium metal)	013-002-00-1	7429-90-5	231-072-3			F; R11-15	
Carbon (Graphite)		7440-44-0	231-153-3				
Phosphorus, red (Phosphorus, yellow)	015-002-00-7	7723-14-0	231-768-7			F; R11 R16 R52/53	

## Sifalloy No 76

Revision 1

Revision date 2015-11-16

## 3.2. Mixtures

## EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
nickel powder. .	028-002-01-4	7440-02-0	231-111-4			Carc. 2: H351; STOT RE 1: H372; Skin Sens. 1: H317; Aquatic Chronic 3: H412;	
Chromium		7440-47-3	231-157-5				
Cobalt	027-001-00-9	7440-48-4	231-158-0			Resp. Sens. 1: H334; Skin Sens. 1: H317; Aquatic Chronic 4: H413;	

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air. Seek medical attention if irritation or symptoms persist.
Eye contact	Avoid contact with eyes. Seek medical attention.
Skin contact	Wash off immediately with plenty of soap and water.
Ingestion	If swallowed, seek medical advice immediately and show this container or label.

## SECTION 5: Firefighting measures

## 5.1. Extinguishing media

	Extinguishing media. Carbon dioxide (CO2). Dry chemical. For large fires:.. Alcohol resistant foam. Water jet.
--	--

## 5.3. Advice for firefighters

	Self-contained breathing apparatus. Wear suitable respiratory equipment when necessary.
--	---

## SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

	Avoid formation of dust. Ensure adequate ventilation of the working area.
--	---

## 6.3. Methods and material for containment and cleaning up

	Sweep up. No specific clean up requirements. Refer to disposal considerations in Section 13.
--	--

## SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

	Wear suitable gloves.
--	-----------------------

## 7.2. Conditions for safe storage, including any incompatibilities

	Keep container tightly closed and dry.
--	--

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

## 8.1.1. Exposure Limit Values

## Sifalloy No 76

Revision 1

Revision date 2015-11-16

## 8.1.1. Exposure Limit Values

aluminium powder (stabilised). . (Aluminium metal)	WEL 8-hr limit ppm: -  WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total 10 inhalable dust: WEL 8-hr limit mg/m3 total 4 respirable dust:	WEL 8-hr limit mg/m3: -  WEL 15 min limit mg/m3: - WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
Carbon (Graphite)	WEL 8-hr limit ppm: -  WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total 10 inhalable dust: WEL 8-hr limit mg/m3 total 4 respirable dust:	WEL 8-hr limit mg/m3: -  WEL 15 min limit mg/m3: - WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
Chromium	WEL 8-hr limit ppm: -  WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 0.5  WEL 15 min limit mg/m3: - WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
Copper (Copper dusts and mists (as Cu))	WEL 8-hr limit ppm: -  WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 1  WEL 15 min limit mg/m3: 2 WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
Copper (Copper fume)	WEL 8-hr limit ppm: -  WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 0.2  WEL 15 min limit mg/m3: - WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
Phosphorus, red (Phosphorus, yellow)	WEL 8-hr limit ppm: -  WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 0.1  WEL 15 min limit mg/m3: 0.3 WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
Silicon	WEL 8-hr limit ppm: -  WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total 10 inhalable dust: WEL 8-hr limit mg/m3 total 4 respirable dust:	WEL 8-hr limit mg/m3: -  WEL 15 min limit mg/m3: - WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:

## 8.2. Exposure controls

	
8.2.1. Appropriate engineering controls	Keep away from foodstuffs, beverages and feed.
8.2.2. Individual protection measures	Use appropriate personal protective equipment.
Eye / face protection	Wear suitable protective clothing and eye/face protection.

## Sifalloy No 76

Revision 1  
Revision date 2015-11-16

## 8.2. Exposure controls

Skin protection - Handprotection	Wear suitable gloves.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.

## SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Appearance	Solid
Colour	Brown
Odour	Characteristic
Melting point	1290 °C

## SECTION 10: Stability and reactivity

## 10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

## 10.6. Hazardous decomposition products

	None.
--	-------

## SECTION 11: Toxicological information

## 11.1. Information on toxicological effects

Skin corrosion/irritation	May cause irritation to skin in susceptible persons.
Respiratory or skin sensitisation	May cause sensitisation by inhalation. Inhalation may cause nausea and vomiting. May cause drowsiness or dizziness.

## SECTION 12: Ecological information

## Further information

	Avoid release to the environment. Refer to special instructions/Safety data sheets.
--	---

## SECTION 13: Disposal considerations

## General information

	This material and its container must be disposed of in a safe way.
--	--

## Disposal methods

	Dispose of in compliance with all. local and national regulations.
--	--

## SECTION 14: Transport information

## 14.1. UN number

	The product is not classified as dangerous for carriage.
--	--

## 14.2. UN proper shipping name

	The product is not classified as dangerous for carriage.
--	--

## 14.3. Transport hazard class(es)

	The product is not classified as dangerous for carriage.
--	--

## 14.4. Packing group

	The product is not classified as dangerous for carriage.
--	--

## 14.5. Environmental hazards

	The product is not classified as dangerous for carriage.
--	--

## 14.6. Special precautions for user

	The product is not classified as dangerous for carriage.
--	--

## Sifalloy No 76

Revision 1

Revision date 2015-11-16

## 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

	The product is not classified as dangerous for carriage.
--	--

## SECTION 15: Regulatory information

## SECTION 16: Other information

## Other information

Revision	This document differs from the previous version in the following areas: 2 - 2.1.2. Classification - EC 1272/2008. 2 - Signal Word. 2 - Precautionary Statement: Prevention. 2 - Precautionary Statement: Response. 2 - Precautionary Statement: Storage. 2 - Precautionary Statement: Disposal.
Text of risk phrases in Section 3	R11 - Highly flammable. R15 - Contact with water liberates extremely flammable gases. R16 - Explosive when mixed with oxidising substances. R40 - Limited evidence of a carcinogenic effect. R42/43 - May cause sensitisation by inhalation and skin contact. R43 - May cause sensitisation by skin contact. R48/23 - Toxic: danger of serious damage to health by prolonged exposure through inhalation. R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R53 - May cause long-term adverse effects in the aquatic environment.
Text of Hazard Statements in Section 3	Skin Sens. 1: H317 - May cause an allergic skin reaction. Carc. 2: H351 - Suspected of causing cancer . STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure . Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled. Aquatic Chronic 4: H413 - May cause long lasting harmful effects to aquatic life.

## General information

	The information supplied in this safety data sheet is designed only as guidance for safe use, storage and handling of the product. This information relates only to the specific goods listed and may not be valid for such material used in combination with any other product(s). This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy.
--	--