

PRODUCT INFORMATION

HOSE COUPLERS

DESCRIPTION

A hose coupler is used in association with two hose nuts and two hose tails to join two pieces of hose together.



DA4001414LH

FURTHER INFORMATION

Weldability stock couplers to take combinations of 3/8" and 1/4" hose nuts, which can be used in accordance with the appropriate hose tails for the size of the hoses to be connected.

Right-hand threaded nuts and couplers are typically used in oxygen and argon connections, whereas left-hand threaded nuts and couplers, bearing the universal indicator notches, are used with acetylene and propane connections.

NOTES

Weldability stock a complete range of gas equipment, which features many hose attachments. These attachments include hose tails (DA2001414 – DA2003856), splicers (DA30014 – DA30056), hose couplers (DA4001414LH – DA4003838RH), hose check valves (DA5001414LH – DA5003856RH) and adaptors (DA6003814BLH – DA6003814SRH).

All are manufactured to high levels of quality to help ensure a leak-proof gas line.

ARTICLES & ACCESSORIES

Part Number	Product Description
DA4001414LH	1/4" – 1/4" HOSE COUPLER LH
DA4001414RH	1/4" – 1/4" HOSE COUPLER RH
DA4003814LH	3/8" – 1/4" HOSE COUPLER LH
DA4003814RH	3/8" – 1/4" HOSE COUPLER RH
DA4003838LH	3/8" – 3/8" HOSE COUPLER LH
DA4003838RH	3/8" – 3/8" HOSE COUPLER RH

TECHNICAL INFORMATION

All measurements are to BSP imperial standards.

For further information, contact Weldability | Sif technical support on **0870 330 7757** or email service@weldability-sif.com



Registered in England No. 1684362
Registered Office: as above

Doc Ref: WELDABILITY/PI/DA4001414LH